



Acrylic Sealer 2600

Technical Data Sheet

Product Description

Kretus Acrylic Sealer 2600 is formulated with aliphatic polymers using fast drying solvents. Properly applied, Kretus Acrylic Sealer 2600 dries to a clear, abrasion resistant film which provides a weatherproof sealer that is resistant to the sun, moisture, industrial chemicals, oil, grease, and most caustic cleaning agents. Test for solvent resistance. Kretus Acrylic Sealer 2600 will extend the surface life to organic surfaces. When properly applied, its exceptional penetrating properties will seal concrete and other surfaces keeping them easy to clean and maintain. Regular cleanup and maintenance procedures can be easily implemented. Kretus Acrylic Sealer 2600 will not yellow and will enhance the natural color of concrete. Multiple coats will increase the gloss to desired level. Areas showing excessive wear can be re-coated when desired.

Applications

For use over Stone, Concrete floors, driveways and other natural surfaces where high quality, light stable sealing requirements are mandatory.

Concrete Preparation

Surfaces to be sealed must be clean, dry, and free of oil, stains and silicone compounds. Do not apply Kretus Acrylic Sealer 2600 until all traces of curing compounds have been completely dissipated. Substrate to be coated must be moisture free. Dries to touch in 30 minutes and may be opened to normal traffic after 2 hours, heavy traffic after 24 hours. Do not apply if air temperature and/ or temperature of substrate are less than 50 degrees F. Excellent for use over colored concrete, expect a slight color change. Kretus Acrylic Sealer 2600 will enhance colors. Always, do a test panel for approval. **DISARM ALL SPRINKLER SYSTEMS 48 HOURS PRIOR TO APPLICATION AND DURING CURE TIME.**

Application Instructions

Kretus Acrylic Sealer 2600 may be applied by a brush, roller, lamb's wool applicator or industrial sprayer. Avoid any excessive buildup or puddling of product. Kretus Acrylic Sealer 2600 may be applied in multiple coats to achieve desired degree of protection and gloss.

Coverage: Approximately 400 - 600 sq. ft. per gallon, depending on substrate and application method.

Note: Test a small area before applying. NEVER THIN MORE THAN 10% BY VOLUME USING ACETONE!

Clean-up

Equipment should be immediately cleaned with Acetone.

Safety

Use only in well ventilated areas. Always use gloves, protective eyewear and clothing. Overexposure to this product may cause SERIOUS HEALTH RISKS. If ingested do not induce vomiting, call a physician immediately.

Caution

Product is extremely flammable keep away from open flames.

Warranty

Kretus products are warranted for 12 months from the date of manufacturing when kept in the original unopened container. Please refer to the Limited Material warranty for additional clarification.

Physical Properties

Boiling Point	Over 285 degrees F
Evaporation Rate: Less than 1	(n-Butyl Acetate = 1)
% Volatile by Weight	38 —49 (Theoretical)
Vapor Density	Not Determined

HAZARDOUS COMPONENTS	CAS#	% by Weight	Vapor Pressure
Component			
Mineral Spirits	64742-47-8	14-18	2.60
Light Aromatic Naphtha	64742-95-6	16-24	Less 10.0 @25 C
Proprietary Solvent, VOC exempt	98-56-6	7-11	N/A

QUEST BUILDING PRODUCTS ♦ 1129 N. Patt Street, Anaheim CA 92801 ♦ Phone: 714.738.6640 ♦ Fax: 714.738.6950