



Kretus Lithium Densifier

Technical Data Sheet

Description

Kretus Densifier is an economical cost-effective treatment formulated for architectural concrete and terrazzo surfaces to rapidly produce a harder surface that is easy to grind and polish. Its deep-penetrating, non-soluble characteristics provide longer life and higher reflectivity, helping reduce floor maintenance cost. This environmentally friendly treatment reduces alkalinity (efflorescence), improves overall abrasion resistance and reduces dusting. Kretus Densifier is used during the production (grinding and polishing) of concrete or terrazzo surfaces. It is designed to enhance the process, making it easier to re-profile as well as reduce costly wear and damage to diamond abrasives.

When properly installed, Kretus Densifier will not leave surface bloom (whitish film or residual deposits) that are difficult to remove. Simple application requires only one treatment, with no brooming or rinsing (compared to Sodium or Potassium chemistry which requires multiple coats, brooming, rinsing, and hazardous rinse-water disposal). Kretus Densifier will not contribute to alkali-silica reactivity (ASR). Kretus Densifier inhibits alkali salts (efflorescence) and sweating in concrete/masonry surfaces.

Advantages

• Deepens clarity and heightens reflectivity (gloss)
• Penetrates and seals existing hardened floors
• Improves chemical and water resistance
• Increases abrasion resistance
• Reduces alkalinity / efflorescence
• Extends the service life of the floor
• User friendly, non-whitening
• Easy to use and maintain
• Environmentally friendly — VOC compliant
• Interior / exterior use

General Directions

Typical Coverage Rates: Concrete ground to 100-200 grit typically requires an application rate of approximately 400-500 sq. ft. per gallon (12-15m²/L). The application rate is determined by the porosity of the surface. Previously densified floors require less material than non-treated floors.

Application Instructions

1. Grind the concrete to an initial surface profile (100-200 grit). This step opens up the surface ensuring better penetration.
2. Mix, shake or stir thoroughly before applying.
3. Depending on size of work area, product can be applied with a pump up sprayer or a high volume, low-pressure sprayer (HVLP). Apply Kretus Densifier to the surface evenly at the rate of approximately 400-500 sq. ft. per gallon. Lightly broom out any puddles immediately after the material has been applied. Allow material to remain on the surface for 30-45 minutes. **DO NOT LET ANY AREA DRY OUT** during this time. Add more Kretus Densifier as needed in order to maintain a uniformly wet surface.
4. After the material has penetrated and is no longer glistening on the surface, continue grinding and polishing to the intended final surface profile and desired finish. If using a wet polishing method, or on integrally colored concrete, we recommend using an auto scrubber and water to remove residual slurry between abrasive disc grits.
5. Please allow 1 hour Dry time, 6 hours foot traffic, and 12 hours vehicular traffic over surface.

Clean Up

Use water to clean tools and equipment. Treatment is environmentally friendly and requires no special or hazardous disposal methods.

Maintenance

Routine sweeping, mopping, washing and mechanical scrubbing of floors with neutral pH cleaners / water is recommended. **DO NOT USE** acidic or citrus cleaners to maintain the floor.

Professional Use Only

Building Service Cleaning Professionals and Industrial Flooring Contractors only. Not for sale or resale to the general public. Must be applied by trained or certified contractors and / or licensed field service specialists.

Health And Safety Precautions

Kretus Densifier is an aqueous Lithium polysilicate solution. The treatment is alkaline and may cause eye and skin irritation. **KEEP OUT OF THE REACH OF CHILDREN.** Do

Available at: Quest Building Products
1129 N. Patt Street, Anaheim CA 92801 ♦ Phone: 714.738.6640
8860 Kenamar Drive #301 San Diego CA 92121 ♦ Phone 858 586 0864

www.questbuilding.com



Kretus Lithium Densifier

Technical Data Sheet

Not take internally. Avoid prolonged contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting – call physician. Avoid contact with eyes. Protective clothing is recommended. Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet. Kretus Densifier will bond to most surfaces - immediately wash off over spray with water and mild detergent.

CAUTION: Surfaces wet with Kretus Densifier may be slippery.

For Medical Emergencies Only

Call Infotrac (800) 535-5053

Outside USA (352) 323-3500

Disclaimer

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.

Available at: Quest Building Products
1129 N. Patt Street, Anaheim CA 92801 ♦ Phone: 714.738.6640
8860 Kenamar Drive #301 San Diego CA 92121 ♦ Phone 858 586 0864

www.questbuilding.com