

S-8904 Low Gloss Additive™

TECHNICAL DATA SHEET

DESCRIPTION

Super-Krete® Low Gloss Additive™ is an additive formulated to reduce the shine of solvent-based, high-gloss sealers, paints and stains. When mixed according to directions, the gloss will disappear when thoroughly dried.

CSI RELATED SECTIONS

09 90 00 - Painting and Coating

09 96 00 - High Performance Coatings

09 93 00 - Staining and Transparent Finishing

SURFACE PREPARATION

Before any Super-Krete products are applied over concrete, the slab must be free of sealers, any type of curing compounds and bond-breakers. Always refer to **Super-Krete Specification S-1** for surface testing, cleaning, preparation and porosity requirements prior to applying Super-Krete products to any concrete surface.

Super-Krete International, Inc. recommends that all Super-Krete applications over concrete first be prepared using Pene-Krete®.

MIXING

Using a metered container, mix 110 grams of Low Gloss Additive into 1 gallon of solvent-based sealer. Stir or mix for 5 minutes to ensure thorough dispersion.

APPLICATION

Apply all products treated with Low-Gloss Additive per manufacturers written instructions.



Coverage Rate

1 kit of Low Gloss Additive will treat 2 gallons of sealer

**Coverage rates will vary, this is an approximation only. Actual coverage will vary due to substrate conditions, surface porosity and method of application.*

Storage

Store in a cool, dry place. Keep from freezing and moisture.

Tools Required

- 5 gallon pail
- Stir sticks
- Drill with paddle mixer attachment
- Gram Scale

Shelf Life

5 years when properly stored.

Packaging

220 Gram Kit

Appearance

White, fine powder

Odor

Sweet

Specific Gravity

1.0271

CAUTION

Keep away from children. Do not take internally. Always use safety gloves, appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist both indoors and outdoors. If ingested, seek medical attention immediately.

LIMITATIONS

Super-Krete products are to be applied only when surface temperatures are above 55° F and rising and not to exceed 100° F. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze. Each Super-Krete product acts as an inherent part of a proven system. Super-Krete products are professional, contractor grade products. Training in the use of these products is available. Consult Super-Krete for information and assistance locating approved contractors in your area or for training class dates. **NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.**

WARRANTY

Super-Krete products are warranted only when applied by Super-Krete Certified Applicators in accordance with Super-Krete specifications. No warranty applies to products applied over concrete substrates with moisture vapor transmissions exceeding (3 lbs.)/(1,000 sf) of surface area. Super-Krete provides a 5 year warranty when products are applied by Certified applicators. To apply for warranty, refer to the Super-Krete Limited Warranty and form filing at www.super-krete.com.

