



1 Contributes
LEED Point

PROSPEC[®]

LEVEL SET PRIMER PLUS

Description

ProSpec[®] Level Set Primer Plus is a highly concentrated film-forming dispersion for priming very dense, smooth non-absorbent substrates such as terrazzo, marble, metal decking, ceramic and quarry tile prior to the installation of the Level Set product.

Features

- Solvent free
- Water based
- Rapid drying
- Excellent bond
- Non-flammable
- Provides maximum adhesion and seal between the substrate and the leveler
- VOC compliant

Uses

For use over:

- Wooden substrates including plywood
- Steel
- Cutback adhesive
- Most non-porous subfloors
- Moisture mitigation coatings

NOTE: All Level Set products must be used in conjunction with a Level Set primer. See individual product data sheets.

Technical Data

Color Wet/Dry

Green

Density

1.0 kg / liter

Drying Time

1-2 hours @ 70° F (21° C)

Flash Point

None

Flammability

Non-flammable

VOC Compliant

Preparation

All substrates must be clean and primed before Level Set Products are applied. Surfaces must be solid, completely clean, free of oil, wax, grease, sealers, curing compounds, asphalt, paint, dirt, loose surface material and any contaminants that act as a bond breaker. Weak concrete surfaces

must be cleaned down to a solid sound substrate by mechanical means. Acid etching or chemical is not acceptable. Thoroughly abrade any dense, smooth or metal surfaces. Cutback and adhesives must be thin and have a solid bond to the subfloor. Remove all dust by mopping and vacuuming.





PROSPEC[®]

LEVEL SET PRIMER PLUS

Mixing

Before using, allow Primer Plus to come to room temperature (65° F (13° C)). This will facilitate easier mixing. Shake the container and apply a THIN, even coat of primer to the substrate using a fine pore foam roller. DO NOT spray, broom or mop apply and leave no bare spots. Avoid puddling and excess accumulations. Remember to leave a thin coat. Heavy, thick applications can be detrimental to the Level Set self-leveling products.

Allow to dry, usually 4-6 hours at an ambient temperature of 70° F (21° C) and relative humidity of 50%. High humidity and low temperatures may extend drying time to 24 hours. The subsequent application of the Level Set product should be within 2 days. However, application of Level Set products can proceed as soon as the primer dries.

Color

Green

Coverage

Approximately 280-450 ft² (26-42 m²) per gallon depending on substrate characteristics.

Packaging

2.64 gal. (10 L) / 22 lb. (10 kg) pail

Storage

Store in a cool dry place. Do not allow to freeze. Always tightly reseal container.

Shelf Life

One year from date of manufacture in the original unopened container.

Clean Up

Use water to clean tools immediately after use.





PROSPEC[®]

LEVEL SET PRIMER PLUS

Best Performance

- Optimum working conditions are between 60-70° F (16-21° C). Low temperatures and high humidity lengthen, and high temperatures and low humidity shorten drying time.
- Apply only a THIN layer of primer within one hour of shaking. Thick layers will provide a soft primer layer resulting in cracking of the Level Set product.
- Apply only over a properly prepared substrate.
- Do not dilute or add admixtures
- Not suitable for use on water soluble adhesive residues
- Always install a test area, insuring suitability of the primer for intended use.
- For interior use only

Caution

- Solvent free. Non-flammable. May cause irritation to eyes, skin or respiratory system
- Avoid contact with eyes or prolonged contact with skin. The wearing of gloves and safety goggles is recommended
- In case of eye contact, flush eyes with potable water and call physician. DO NOT RUB EYES.
- Do not take internally
- Keep out of reach of children and animals
- Provide good ventilation
- Once cured, mixed product presents no ecological risk.
- Consult Material Safety Data Sheet (MSDS) for further information.

First Aid

Skin contact: Wash with water and soap.

Eye contact: Rinse thoroughly with water and consult a doctor.

Ingestion: Do not induce vomiting. Medical help is necessary. Show this label/safety data sheet.



PROSPEC[®]

LEVEL SET PRIMER PLUS

LIMITED 1 YEAR WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American's option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES INCLUDING LOSS OF PROFITS OF ANY KIND.

Product demonstrations are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. This Warranty constitutes the sole warranty given by Bonsal American in connection with this product. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American. Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ProSpec[®] is the registered trademark of Bonsal American, Inc.
8201 Arrowridge Blvd. Charlotte, NC 28273 • www.prospec.com • E-Mail: prospec@oldcastleapg.com

